

6JU8

Quadruple Diode

9-PIN MINIATURE TYPE

For Phase-Detector and Noise-Immune Color-Killer Circuits in Color-Television Receivers, and for FM-Stereo-Multiplex Equipment

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Voltage (AC or DC) 6.3 ± 0.6 volts

Current at heater volts = 6.3 0.600 amp

Peak heater-cathode voltage (Each unit):

Heater negative with
respect to cathode. 300 max. volts

Heater positive with
respect to cathode. 300 max. volts

Direct Interelectrode Capacitances (Approx.):^a

Plate of unit No.1 & cathode of
unit No.2 to cathode of unit No.1 . . . 1.8 μf

Plate of unit No.1 & cathode of
unit No.2 to plate of unit No.2 . . . 2.2 μf

Plate of unit No.2 to internal shield
and heater. 0.62 μf

Plate of unit No.3 & cathode of
unit No.4 to cathode of unit No.3 . . . 1.9 μf

Plate of unit No.3 & cathode of unit
No.4 to plate of unit No.4. 2.2 μf

Plate of unit No.4 to internal shield
and heater. 0.94 μf

Cathode of unit No.1 to internal shield
and heater. 1.8 μf

Cathode of unit No.3 to internal shield
and heater. 1.9 μf

Mechanical:

Operating Position. Any

Type of Cathodes. Coated* Unipotential

Maximum Overall Length. 2-5/8"

Maximum Seated Length. 2-3/8"

Length, Base Seat to Bulb Top (Excluding tip). 2" $\pm 3/32$ "

Diameter. 0.750" to 0.875"

Dimensional Outline See *General Section*

Bulb. T6-1/2

Base. Small-Button Noval 9-Pin (JEDEC No.E9-1)




RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA
5-62

6JU8

Basing Designation for BOTTOM VIEW. 9PQ

Pin 1-Plate of
Unit No.4
Pin 2-Plate of
Unit No.3,
Cathode of
Unit No.4
Pin 3-Cathode of
Unit No.3
Pin 4-Heater
Pin 5-Heater



Pin 6-Internal
Shield
Pin 7-Plate of
Unit No.2
Pin 8-Plate of
Unit No.1,
Cathode of
Unit No.2
Pin 9-Cathode of
Unit No.1

Maximum Ratings, Design-Maximum Values:

Values are for Each Unit

PEAK INVERSE PLATE VOLTAGE. 300 max. volts
PEAK PLATE CURRENT. 54 max. ma
DC OUTPUT CURRENT 9 max. ma


Characteristics, Instantaneous Value:

Values are for Each Unit

Plate Current for plate volts = 10. 60 ma

^a Without external shield.

ARRANGEMENT OF DIODE UNITS



92CS-11532R1

